



EG Series Screw Air Compressors

Life source of industries

ELGI

Always Better.

UPTIME[™]
ASSURANCE



CIN: L29120TZ1960PLC000351

www.elgi.com

11 - 75 kW / 15 - 100 HP (60Hz)



A Tradition of Reliability

ELGi, established in 1960, designs and manufactures a wide range of air compressors. The company has gained its reputation for design and manufacture of screw compressors through strategic partnerships and continuous research and development. Over the years, it has emerged as a multi-product, multi-market enterprise providing total compressed air solutions in all segments. ELGi's design capabilities translated into a wide range of products ranging from oil-lubricated and oil-free rotary screw compressors, reciprocating compressors and centrifugal compressors. ELGi has its own manufacturing operations in India, Italy and USA with subsidiaries in Australia, Brazil, UAE and Indonesia. The company is fast expanding its global footprint attracting distributors and customers with its latest generation products.



Robust Infrastructure

ELGi has modern manufacturing facilities equipped with advanced high precision grinding machines, turning centres and CNC horizontal and vertical machining centres. Screw airends are manufactured with the latest rotor grinding technology, coupled with measurement technology to maintain precise manufacturing tolerances. ELGi's manufacturing plants are both ISO and EOHS certified. The products are manufactured under controlled environment to ensure that its quality continues to meet the highest standards.



Innovative Technology

Screw Compressor elements are manufactured in-house using state-of-the-art machining centres for rotor grinding and machining castings of various sizes. ELGi's own eta-V profile rotors ensure energy-efficient compressed air supply for all demanding applications. ELGi is one of the few companies capable of manufacturing wide range of airends and compressor packages in the world. ELGi's patent portfolio is a testament to the company's continuous research and innovation capability




AIR UP.

UPTIME™ comes standard on every EG Series Compressor



UPTIME Design

This speaks to the engineering and design of our products. Our R&D is dedicated to designing machines that run cooler, cleaner and longer... that are easy to service... with longer service intervals.



UPTIME Components

For so many of our customers, seeing is believing. They know a quality-built machine when they see it. That's why every part on a ELGi compressor is a quality part. From our proprietary air ends, to our use of leak-free hoses and piping.



UPTIME Assurance

Here is where we back our pledge, Our industry leading warranties, parts availability and call centers staffed by experts assure peace-of-mind to our customers.



The EG Series compressors represent a giant leap in design and performance with each component designed for reliability and ease of maintenance. The compressor is manufactured in compliance with applicable international standards (UL, ASME, CE and others) and designed as per the international quality standards. These new generation compressors significantly reduce operating costs and provide cost savings with fast return on investment.

Two-Stage Air Filtration
Increased life of consumables

High Volumetric Efficiency
Low energy cost per cfm

Advanced Neuron III Controller (Remote management of compressor operations)
Ready for SCADA/DCS

Highly Efficient Motor
Energy cost savings

Option of VFD
Compact and saves floor area

Enclosure Designed to Industrial Standards
Silent, aesthetic package

Superior Technology Airend
Gearless* and reduced sound

Robust Cooling System
Reduced air outlet temperature

Safety Compliant Package

EG Series - The Technology Edge



*for selected models only

EG Series

The Eco-friendly
Energy-efficient compressors



Save energy
High efficient airend



ELGI's airends are equipped with in-house developed eta-V profile rotors, with 4/5 lobe combination, the rotors are designed to run at optimum speeds. This unique design reduces pressure losses and increased efficiencies. The rotors ensure energy-efficient compressed air supply for all demanding applications.

- Precise rotor clearances for best-in-class energy efficiency
- Low operating speeds for long life, low maintenance and low sound level
- Complies with applicable safety standards



Reduced starting load
Intake valve system

The new generation intake valve with integrated blow down unit, solenoid controls and actuators is designed for low losses. Intake valve optimally controls the compressor capacity during startup reducing the no-load power. This optimal capacity control results in direct savings on power consumption





Oil-Less Air(1ppm)* Efficient air-oil separation with OSBIC(3 Stages)

ELGi has applied unique OSBIC process (Oil Separation By Impact and Centrifugal action) which enables efficient separation of air and oil, with minimum pressure drop. The method enables separation of oil in three stages, delivering consistent oil-free air while increasing the life of separator element

* as per ISO Standards



Moisture-Free Air 99% Water Free

Depending on the humidity level of inlet air, bulk water remains in compressed air at varying levels and causes corrosion of piping, end tools, machinery and valves. EG Series air compressor has a custom-designed centrifugal type moisture separator with an automatic drain. This comes as a part of the package at no extra cost and removes over 99% of bulk water from the compressed air, resulting in corrosion free, longer life of end use equipments and less load on the dryer



Cool Air Efficient air cooling

The cooling system with fans and larger cooling surface area enhances the cooling of hot air. The fan motor uses significantly low power. The integrated fan-motor assembly maintains low temperature there by increasing the life of motor. Smart cooling system design enables easy maintenance and ducting. More over, the complete system is insulated internally from other zones



Robust and Reliable Reliability under extreme conditions

EG series compressors are designed to perform at extreme temperatures - from cold to hot and from dry to extremely humid conditions





Performance Control System

- Built-in Dryer Dew Point integration
- VFD Parameter (Power, HMR, Frequency, Ampere, Voltage)
- Read out and closed loop control
- Selectable AO (Pressure/Temperature/Dew Point) for DCS integration
- Controlled drain system



Reports

- Cumulative Report (Run hours, load hours, unload hours, stop hours, fault hours and remaining AFCT, OFCT, OSCT, OCT and RGT)
- Detail Report - Previous 15 days (Load hours, unload hours, stop hours, fault hours, and number of times machine stopped due to standby)
- Fault Report - (Previous 99 faults in chronological order with real time stamping and type of fault)



Remote Monitoring

- **DCS (MODBUS RTU/RS 485):** controller is enabled to synchronize with distributed control system - control of compressor from control panel of customer
- **SCADA :** compressor control through PC with remote monitoring by supervisory control and data acquisition process



Safety and Protection


Global Series compressors are designed and perfected to ensure highest level of safety for

- Pressure regulating valve
- High pressure
- High temperature
- Pressure relief valve
- Phase order and single phase

Compressor Near Point of Use

Compressors can be placed anywhere in assembly area without any special foundation

- Low Sound
- Low Vibration
- Compact



ELGi Airmate Accessories

Airmate Particulate Filter

Air Flow: 35 - 3,200 cfm
Working Pressure: 100 - 190 psi
(7 - 13 bar)
Filtration Range: 1 - 0.003 microns



Refrigeration air dryer

Capacity: 10 - 2000 cfm
Working pressure: 100 - 870 psi
(7 - 60 bar)
Filtration range: +3°C. PDP



Airmate Air Receiver

Capacity : 250 - 10000 ltrs
Working Pressure : 100 - 190 psi
(7 - 13 bar)
Code of Construction: ASME sec.
VIII Div.I or IS 2825



Drain Valves

Timer controlled and zero loss
Capacity : 50 to 2000 cfm
Working Pressure: 100 - 190 psi
(7 - 13 bar)



Cooler Pre-filter

Available for all the models
as an optional accessory



After Sales Solutions

A wide range of After Sales products and services is designed to add maximum value for our customers. Our fast serviceability ensures optimum availability and reliability of the compressors with the lowest possible operating costs

Genuine Spares and Service


ELGi Genuine Spares helps in avoiding unexpected compressor failures and the risk of consequential damage to other vital compressor components. ELGi spares are designed, manufactured and checked for quality to meet the standards of a new compressor. The spares undergo continuous improvement to provide best results and are available through the vast network of ELGi dealers in India and International markets

Genuine Spares

For enhancing performance and productivity



Air/Oil Flow Diagram



1. Air Intake Filter
2. Suction Control Valve
3. Aired
4. Drive Coupling
5. Electric Motor
6. Air-Oil Separator Tank
7. Minimum Pressure Valve
8. Cooling Fan
9. After Cooler
10. Moisture Separator
11. Automatic Drain
12. Outlet Valve
13. Oil Cooler
14. Air-Oil Separator
15. Oil Filter (spin-on)
16. Thermal Valve Unit

- COOLED AIR
- HOT AIR
- COOLED OIL
- HOT OIL
- HOT AIR/OIL MIXTURE

Energy Saving - The CONSERVE Way

In-Built ELGi **CONSERVE**™ Variable Frequency Drives (VFD)

Matches compressor output with demand by varying motor speed. The power consumption reduces in line with the reduction in demand. This Helps in eliminating the frequent load-unload cycle and also the wasted power from the energy bill.

A fixed speed compressor operates on a load unload band of at least 10 psi around the working pressure whereas with ELGi VFD, compressor can be operated within a band of 2 psi. Since the compressor is not operated under higher than working pressure requirements, there is substantial energy saving. For every 2 psi reduction in operating pressure, there is 1% power saving.

In a fixed speed compressor with Star-Delta starter, starting current is as high as three times the full load current (FLC). With ELGi VFD starting, starting current is less than the FLC. This helps to avoid using heavy rated components like fuses, MCCB, cable size, generator rating, isolators etc.

For compressed air systems with fluctuating demand pattern, giving a fast return on investment .



Advantages:


Electrical:

- Low starting current
- High efficiency
- Improved power factor
- Reduced maximum demand


Mechanical:

- Minimum maintenance
- Smooth start
- Smooth control

10 Year Life-Cycle Cost




Compressor without VFD



Compressor with **CONSERVE**™

- Electricity Cost
- VFD Saving
- Equipment Cost
- Maintenance Cost

Dimensional Data



Technical Specification

Model	Motor Power		Working Pressure		Maximum Pressure		Free Air Delivery		Weight	Noise Level
	60 Hz	kW	HP	bar g	psi g	bar g	psi g	m ³ /min	cfm	(Kg)
Length : 1425mm Breadth : 720mm Height : 1470mm										
EG 11	11	15	6.9	100	7.4	107	2.01	71	590	69
EG 11	11	15	8.6	125	9.1	132	1.81	64	590	69
EG 11	11	15	10.3	150	10.8	157	1.61	57	590	69
EG 11	11	15	12.1	175	12.6	182	1.39	49	590	69
EG 15	15	20	6.9	100	7.4	107	2.61	92	610	69
EG 15	15	20	8.6	125	9.1	132	2.41	85	610	69
EG 15	15	20	10.3	150	10.8	157	2.21	78	610	69
EG 15	15	20	12.1	175	12.6	182	1.95	69	610	69
EG 18	18	25	6.9	100	7.4	107	3.28	116	680	69
EG 18	18	25	8.6	125	9.1	132	3.03	107	680	69
EG 18	18	25	10.3	150	10.8	157	2.58	91	680	69
EG 18	18	25	12.1	175	12.6	182	2.27	80	680	69
EG 22	22	30	6.9	100	7.4	107	3.96	140	690	69
EG 22	22	30	8.6	125	9.1	132	3.74	132	690	69
EG 22	22	30	10.3	150	10.8	157	3.17	112	690	69
EG 22	22	30	12.1	175	12.6	182	2.69	95	690	69
Length : 1705mm Breadth : 1111mm Height : 1570mm										
EG 30	30	40	6.9	100	7.4	107	5.75	203	990	68
EG 30	30	40	8.6	125	9.1	132	5.13	181	990	68
EG 30	30	40	10.3	150	10.8	157	4.30	152	990	68
EG 30	30	40	12.1	175	12.6	182	3.85	136	990	68
EG 37	37	50	6.9	100	7.4	107	6.99	247	1110	69
EG 37	37	50	8.6	125	9.1	132	6.06	214	1110	69
EG 37	37	50	10.3	150	10.8	157	5.44	192	1110	69
EG 37	37	50	12.1	175	12.6	182	4.84	171	1110	69
EG 45	45	60	6.9	100	7.4	107	8.49	300	1140	68
EG 45	45	60	8.6	125	9.1	132	7.53	266	1140	68
EG 45	45	60	10.3	150	10.8	157	6.26	221	1140	68
EG 45	45	60	12.1	175	12.6	182	5.58	197	1140	68
Length : 1961mm Breadth : 1265mm Height : 1775mm										
EG 55	55	75	6.9	100	7.9	115	10.62	375	1750	69
EG 55	55	75	8.6	125	9.7	140	9.83	347	1750	69
EG 55	55	75	10.3	150	11.4	165	8.01	283	1750	69
EG 55	55	75	12.1	175	13.1	190	7.42	262	1750	69
Length : 2063mm Breadth : 1269mm Height : 1969mm										
EG 75	75	100	6.9	100	7.9	115	14.95	528	2020	69
EG 75	75	100	8.6	125	9.7	140	12.83	453	2020	69
EG 75	75	100	10.3	150	11.4	165	11.75	415	2020	69
EG 75	75	100	12.1	175	13.1	190	11.04	390	2020	69

Note:

Free Air Delivery(FAD) is tested as per ISO 1217 : 2009 Annexure C Edition: 4

All standard models are air-cooled

Sound level measures as per ISO 2151, Second Edition at 1m distance in field conditions, +/- 3dB(A)

Due to continuous improvements, the specifications are subject to change without prior notice

Product images displayed in this brochure are only representative and may not exactly match the actual product

Technical Specification - VFD Model

Model	Motor Power		Working Pressure		Maximum Pressure		Free Air Delivery		Weight	Noise Level
	60 Hz	kW	HP	bar g	psi g	bar g	psi g	m ³ /min		
Length : 1425mm Breadth : 720mm Height : 1470mm										
EG 11	11	15	6.9	100	7.4	107	0.76 ~ 2.01	27 ~ 71	640	69
EG 11	11	15	8.6	125	9.1	132	0.76 ~ 1.84	27 ~ 65	640	69
EG 11	11	15	10.3	150	10.8	157	0.76 ~ 1.61	27 ~ 57	640	69
EG 11	11	15	12.1	175	12.6	182	0.65 ~ 1.39	23 ~ 49	640	69
EG 15	15	20	6.9	100	7.4	107	1.05 ~ 2.61	37 ~ 92	690	69
EG 15	15	20	8.6	125	9.1	132	1.02 ~ 2.44	36 ~ 86	690	69
EG 15	15	20	10.3	150	10.8	157	1.02 ~ 2.21	36 ~ 78	690	69
EG 15	15	20	12.1	175	12.6	182	0.91 ~ 1.95	32 ~ 69	690	69
EG 18	18	25	6.9	100	7.4	107	1.56 ~ 3.28	55 ~ 116	710	69
EG 18	18	25	8.6	125	9.1	132	1.42 ~ 3.03	50 ~ 107	710	69
EG 18	18	25	10.3	150	10.8	157	1.19 ~ 2.58	42 ~ 91	710	69
EG 18	18	25	12.1	175	12.6	182	1.02 ~ 2.27	36 ~ 80	710	69
EG 22	22	30	6.9	100	7.4	107	1.84 ~ 3.96	65 ~ 140	716	69
EG 22	22	30	8.6	125	9.1	132	1.73 ~ 3.74	61 ~ 132	716	69
EG 22	22	30	10.3	150	10.8	157	1.50 ~ 3.17	53 ~ 112	716	69
EG 22	22	30	12.1	175	12.6	182	1.19 ~ 2.69	42 ~ 95	716	69
Length : 1705mm Breadth : 1111mm Height : 1570mm										
EG 30	30	40	6.9	100	7.4	107	2.12 ~ 5.75	75 ~ 203	1040	68
EG 30	30	40	8.6	125	9.1	132	2.07 ~ 5.13	73 ~ 181	1040	68
EG 30	30	40	10.3	150	10.8	157	2.04 ~ 4.30	72 ~ 152	1040	68
EG 30	30	40	12.1	175	12.6	182	1.84 ~ 3.85	65 ~ 136	1040	68
EG 37	37	50	6.9	100	7.4	107	2.63 ~ 6.99	93 ~ 247	1160	69
EG 37	37	50	8.6	125	9.1	132	2.61 ~ 6.06	92 ~ 214	1160	69
EG 37	37	50	10.3	150	10.8	157	2.58 ~ 5.44	91 ~ 192	1160	69
EG 37	37	50	12.1	175	12.6	182	2.29 ~ 4.84	81 ~ 171	1160	69
EG 45	45	60	6.9	100	7.4	107	3.14 ~ 8.50	111 ~ 300	1190	68
EG 45	45	60	8.6	125	9.1	132	3.11 ~ 7.53	110 ~ 266	1190	68
EG 45	45	60	10.3	150	10.8	157	2.97 ~ 6.26	105 ~ 221	1190	68
EG 45	45	60	12.1	175	12.6	182	2.63 ~ 5.58	93 ~ 197	1190	68
Length : 1961mm Breadth : 1265mm Height : 1775mm										
EG 55	55	75	6.9	100	7.9	115	3.96 ~ 10.62	140 ~ 375	1820	69
EG 55	55	75	8.6	125	9.7	140	3.94 ~ 9.83	139 ~ 347	1820	69
EG 55	55	75	10.3	150	11.4	165	3.62 ~ 8.01	128 ~ 283	1820	69
EG 55	55	75	12.1	175	13.1	190	3.57 ~ 7.59	126 ~ 268	1820	69
Length : 2063mm Breadth : 1269mm Height : 1969mm										
EG 75	75	100	6.9	100	7.9	115	6.14 ~ 14.95	217 ~ 528	2150	69
EG 75	75	100	8.6	125	9.7	140	6.12 ~ 12.83	216 ~ 453	2150	69
EG 75	75	100	10.3	150	11.4	165	5.38 ~ 11.75	190 ~ 415	2150	69
EG 75	75	100	12.1	175	13.1	190	5.30 ~ 11.04	187 ~ 390	2150	69

Note:

Free Air Delivery (FAD) is tested as per ISO 1217 : 2009 Annexure E Edition: 4

All standard models are air-cooled

Sound level measures as per ISO 2151, Second Edition at 1m distance in field conditions, +/- 3dB(A)

Due to continuous improvements, the specifications are subject to change without prior notice

Product images displayed in this brochure are only representative and may not exactly match the actual product

Compressed air solutions for all sustainable air needs



Oil-Free Series Screw
90 - 450 kW / 480 - 2515 cfm



EG Series Rotary Screw
11 - 250 kW / 47 - 1612 cfm



EN Series Rotary Screw
2.2 - 75 kW / 8.0 - 469 cfm



Electric Portable (Trolley)
22 - 75 kW / 131 - 490 cfm



Diesel portable (Trolley)
185 - 1100 cfm / 100 - 300 psi



Diesel Portable (Skid)
475 - 1500 cfm / 150 - 400 psi



Oil-free Recip
1.0 - 75 HP / 1.8 - 300 cfm



Oil-lubricated Recip
1.0 - 40 HP / 2.0 - 128 cfm

OVERSEAS OFFICES:

Bangladesh : ELGI Equipments Limited, 5th Floor, Planners Tower, Level: 5 Suite: 8-13, 13/A Bir Uttam CR Datt Road, Sonargaon, Dhaka-1000. Bangladesh. **T:** 880-9671453-65, **F:** 880-28616148, **E:** bangladesh-enquiry@elgi.com

Malaysia : ELGI Equipments Limited, No 2A-4-6, Jalan Jubli Perak, 22/1, Section 22, 40400, Shah Alam, Malaysia, **T:** +603 55693544, **F:** +603-55693544, **E:** malaysia-enquiry@elgi.com, **w:** www.elgi.com.my

Srilanka : S.G. Arcade, 2nd Floor, No.441, Sri Sangaraja Mawatha, Colombo-10, **T:** 00 - 94-11-2392425, **F:** 00-94-11-4737412. **E:** elgisupport@slnet.lk

Thailand : ELGI Equipments Limited, 223/66 Country Complex A 14th Floor, Sanphawut Road, Bangna Bangkok - 10260. **T:** +6627455160 **E:** thailand-enquiry@elgi.com, **w:** www.elgi.co.th

WHOLLY OWNED SUBSIDIARIES

Australia : ELGI Equipments Australia Pvt Ltd., 38. Richland Avenue, Coopers Plain QLD 4108 Australia. **T:** +61-7-3106 0589, **F:** +61-7-3106 0537, **E:** Enquiry@elgi.com.au, **w:** www.elgi.com.au

Brazil : ELGI Compressores Do Brasil Ltd., Av. Emilio Checchinato, 4195 - B: Cep : 13295 - 000, Bairro: Sao Roque da Chave: Itupeva - SP, Brazil. **T:** 4496 5519, 4496 6611, **E:** contacto@elgi.com.br, **w:** www.elgi.br

China : **ELGI Equipments (Zhejiang) Limited**, No.232, Yunhai Road, Economic Development Zone, Jiaxing 314033 P. R. China **T:** +86-573-82079100 Hotline: 400-826-3585 | **ELGI Compressors Trading (shanghai) Co. Ltd.**, Rm 909, LSHQ International Centre, 288 Hongjing Road, Shanghai 201103, P. R. China **T:** +86-21-33581191 Hotline: 400-826-3585, **E:** enquiry.cn@elgi.com, **w:** www.elgi.com.cn

Indonesia : PT ELGI Equipments Indonesia, Kawasan Pergudangan, BIZPARK Commercial Estate, Pulogadung Jl. Raya Bekasi KM 21, 5 Blok A3 No. 12, Kel. Rawa Terate, Kec. Cakung, Pulogadung Jakarta Timur 13920. **T:** +62-21-46822216, 46827388, **E:** indonesia-enquiry@elgi.com, **w:** www.elgi.co.id

Italy : ELGI Compressors Italy S.r.l., Rome(RM), Via Del Babuino 51, 00187 : ROTAIR Spa, Via Bernezzo 67, 12023 Caraglio (CN), Italy. **T:** +39 0171619676, **F:** +39 0171619677, **E:** info@rotairspa.com

Middle East : ELGI Gulf (FZE), P.O. Box: 120695, Q4-081, SAIF Zone, Sharjah, U.A.E. **T:** +971 6 557 9970, **F:** + 971 6 557 9980, **E:** gulfenquiry@elgi.com

USA : ELGI Compressors USA, Inc. 1500-N Continental Blvd, Charlotte, NC 28273. **T:** +1-704-943-7966, **M:** +1-803-427-7985, **W:** www.elgi.us

ELGI

ELGI EQUIPMENTS LIMITED

CORPORATE OFFICE: Trichy Road, Singanallur, Coimbatore - 641005,

T: +91-422-2589555, **E:** enquiry@elgi.com, **w:** www.elgi.com

Distributed by

